

HSF


NOTES:

Current Rating: 8A
 Voltage Rating: 300V
 Contact Resistance: 8milliohm Max
 Withstand Voltage: AC 1500V
 Insulation Resistance: 1000Megohm Min
 Screw Torque: 2 lbf.in
 Wire range: 16-30AWG
 Operation Temperature: -40°C to +105°C

Ordering Information:


P F 381 - C XX A SM N 1 N

F=Female Pitch 381=3.81 No.of Pins 02-20P Contact Plated SM=Matte Tin Blank=W/T WCON Logo N=W/O WCON Logo
 Color A=Green N=Without Type A1 Two Side Screw
 W/T WCON LOGO



11P	42.30 ±0.30	38.10 ±0.30			
10P	38.49 ±0.30	34.29 ±0.30	20P	76.59 ±0.40	72.39 ±0.40
9P	34.68 ±0.30	30.48 ±0.30	19P	72.78 ±0.40	68.58 ±0.40
8P	30.87 ±0.20	26.67 ±0.20	18P	68.97 ±0.40	64.77 ±0.40
7P	27.06 ±0.20	22.86 ±0.20	17P	65.16 ±0.40	60.96 ±0.40
6P	23.25 ±0.20	19.05 ±0.20	16P	61.35 ±0.40	57.15 ±0.40
5P	19.44 ±0.20	15.24 ±0.20	15P	57.54 ±0.40	53.34 ±0.40
4P	15.63 ±0.20	11.43 ±0.20	14P	53.73 ±0.30	49.53 ±0.30
3P	11.82 ±0.20	7.62 ±0.20	13P	49.92 ±0.30	45.72 ±0.30
2P	8.01 ±0.20	3.81 ±0.10	12P	46.11 ±0.30	41.91 ±0.30
位数	A	B	位数	A	B

(5)	Contact	TPT031-PSM001	N	C5191R-H T=0.3mm
(4)	Pin Block	BL020-1BNI01	N	C3604
(3)	Screw	MA020-1SXX01	N	C1018
(2)	Cover	XPC381-XXB1XN1	1	PA66 UL94-V0
(1)	Housing	XPF381-XXB1XN1(N)	1	PA66 UL94-V0
ITEM	TITLE	P/N	Q'TY	Material

A3	2020/07/28	ADD LOGO; ADD W/O LOGO P/N	A3	XSR	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.	 Http: www.wcon.com WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: salesks@wcon.com
A2	2018/04/12	Modify Terminal ; Add DIM.	A2	XSR	x.x ±0.40	XSR	2020/07/28	UNIT	mm	TITLE:	
A1	2015/07/15	Modify	A1	XSR	x.xx ±0.25	CHECK	DATE	SIZE	A4	3.81mm Pitch Female Pluggable Terminal Blocks	
A0	2012/05/14	NEW			x.xxx ±0.15	APPROVE	DATE	SHEET	1/1	Customer NO.	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE		Angle ± 3° DIM TOL			PROJ.			